



RHD 1-4

ISOLATOR

Description

Isolator in neoprene.

It is available in 4 different hardness, which is easy to identify by paint marking.

Natural frequency: 7 - 10 Hz

Weight: 0,25 – 2,7 kg.

Applications

Elastic suspension of pipes, fans etc. Not suitable for out door applications, then spring isolators are recommended.

Type	Max. load (kg)	Max. defl. (mm)	Dimensions (mm)							
			L	W	H	A	B	C	D	
RHD-1	Blue	16	10	57	51	76	35	19	9,5	10
	Black	20								
	Red	34								
	Green	55								
RHD-2	Black	76	12,6	76	57	114	48	30	16	18
	Red	110								
	Green	170								
	Grey	250								
RHD-3	Black	114	12,6	95	83	159	80	38	19	22
	Red	238								
	Green	340								
	Grey	568								
RHD-4	Black	680	12,6	114	102	208	80	30	25	30
	Red	1020								
	Green	1360								
	Grey	1800								

Type of mounts for steel pipes				
Pipe dimension (mm)		Ca weight (kg)		Recammanded isolator, water filled 3 m:s distance
Outer dia.	Thickness	Dry	With water	
30	2,6	1,77	2,3	1 - blue
57	2,9	3,90	6	1 - black
70	2,9	4,83	8	1 - red
108	3,6	9,33	17	2 - black
133	4,0	12,8	25	2 - red
159	4,5	17,1	35	2 - green
177,8	5,0	21,3	44	2 - green
219	6,3	33,1	66	3 - red
244,5	6,3	37,1	79	3 - green
298,5	7,1	51,1	114	4 - black
355,6	8,0	68,3	158	4 - black