



Vibratec

akustikprodukter

VT4524-2X



Description

Single working all metal telescopic mount. Spring made of high tensile steel.
Resilient element, cushion in stainless steel wire.
Scrolls in aluminium.
Other parts in mild steel.

Characteristics

Mounts with very low natural frequency, 3-4 Hz, depending on preload.
Accepts both static and dynamic tension forces.
Maximum excitation: ± 1 mm.
Mechanical strength: 2 g.
Amplification factor: < 8 .
Temperature range: -90°C to $+300^{\circ}\text{C}$

Ref.	Load range in daN (\approx kg)
VT4524-25	420 - 620
VT4524-26	600 - 840
VT4524-27	700 - 1100

Application

Isolation of exhaust-, air- and steam-pipes.
Stabilisation of frames and equipment on vessels, vehicles etc.

Ref.	A	B	Weight(kg)
VT4524-25	100	120	10,5
VT4524-26	100	120	10,6
VT4524-27	100	120	10,7

Note

For smaller loads, see isolator VT 4525-0X.

For larger loads, see isolator VT 4525-4X

Norway

P.O. Box 765, N-3196 Horten, Norway
Tel: +47 33 07 07 50 Fax: +47 33 07 00 68
e-mail: apn@apn.no

Sweden

Norrsvund 1859, S-760 17 BLIDÖ, Sweden
Tel: +46 176 20 78 80 Fax: +46 176 20 78 99
e-mail: info@vibratec.se