






akustikprodukter







VT-RFH is a series of ReguFoam Hangers available in 4 different load ranges. Housing and washer in zinc plated steel, elastic elements in color coded polyurethane foam.

Characteristics

Deflection:

4 – 8 mm for pads 50 mm

Resonance frequency:

7 – 10 Hz for pads 50 mm

Applications

For elastic pendulum suspension of piping, mechanical equipment, fans, air ducts, loud speakers and inner ceilings. The Regufoam pad acts as a vibration isolator attenuating structure born sound.

| Article Nr. | Load Range | Color |
|---------------|------------|-------|
| VT-RFH-510/50 | 40-80kg | Beige |
| VT-RFH-570/50 | 80-140kg | Pink |
| VT-RFH-740/50 | 140-200kg | Red |
| VT-RFH-810/50 | 180-250kg | Brown |

Note

For smaller loads use VT-MCH.

| Sweden | Norway | Denmark | Estonia |
|--------|--|--|---|
| | Tel: +47 33 07 07 50 e-mail: info@vibratec.no | Tel: +45 49 13 22 44 e-mail: info@vibratec.dk | Tel: +372 56 66 29 93 e-mail: info@vibratec.ee |

We are continuously developing and improving our products and therefore design and specifications in our datasheets may be changed without prior notice

